NSN 5315-01-034-5251

First End Style: Chamfered

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-034-5251

Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Shank Length:
Between 0.178 inches and 0.198 inches
Shoulder Width Across Flats:
Between 0.552 inches and 0.572 inches
Shank Diameter:
Between 0.205 inches and 0.210 inches
Overall Length:
Between 2.522 inches and 2.542 inches
First End Taper Length:
0.032 inches
Second End Taper Length:
Between 0.040 inches and 0.070 inches
Second End Relationship With First End:
Second End Relationship With First End: Identical
·
Identical
Identical Thread Size:
Identical Thread Size: 0.250 inches
Identical Thread Size: 0.250 inches Second Shank Diameter:
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location:
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle:
Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish:
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 250.000 microinches
Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 250.000 microinches Second End Taper Angle:
Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 250.000 microinches Second End Taper Angle: 45.0 degrees
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 250.000 microinches Second End Taper Angle: 45.0 degrees Second Shank Length:
Identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 250.000 microinches Second End Taper Angle: 45.0 degrees Second Shank Length: Between 2.147 inches and 2.167 inches

Qq-s-763, class 302 cond a federal specification single material response

NSN 5315-01-034-5251

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Style Designator:
Shoulder
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0