## NSN 5315-01-035-5534

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-035-5534 **Head Diameter:** Between 0.360 inches and 0.450 inches **Shank Diameter:** Between 0.1870 inches and 0.1885 inches **Ring Handle Diameter:** Between 1.000 inches and 1.125 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** 0.400 inches **Actuation Type:** Pull and push Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Shear Strength:** 4600 double pounds per square inch **Shoulder To Head End Distance:** 1.945 inches Pin Attachment Type: Hook **Detent To Tapered End Distance:** 0.410 inches **Special Features:** Surface balls passivated qq-p-35 Material: Steel head **Material Specification:** Qq-w-423 federal specification 1st material response detent or ams 5673 17-7ph assn standard 3rd material response detent **Surface Treatment:** Passivate ring **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response spring **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5315-01-035-5534

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.