

View Online at <https://aerobasegroup.com/nsn/5315-01-037-4703>

First End Style:

Slotted

Second End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.365 inches and 0.395 inches

Shank Length:

Between 0.365 inches and 0.395 inches

Shoulder Diameter:

Between 0.184 inches and 0.185 inches

Shank Diameter:

0.164 inches

Overall Length:

Between 1.260 inches and 1.265 inches

Undercut Diameter:

Between 0.120 inches and 0.125 inches

Undercut Width:

Between 0.080 inches and 0.090 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.0780 inches and 0.0786 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.086 inches and 0.096 inches

First End Slot Width:

Between 0.040 inches and 0.045 inches

First End Slot Depth:

Between 0.185 inches and 0.195 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.164 inches

First End Location:

Threaded end

Surface Finish:

32.0 microinches shoulder end

Special Features:

Threaded end, passivated, mil-std-171, finish 5.4.1

Material:

Steel comp 416

Material Specification:

Qq-s-764, cond h federal specification single material response

Surface Treatment:

Chromium shank

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0