# NSN 5315-01-038-1348

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-038-1348

## Shank Diameter:

Between 0.2470 inches and 0.2485 inches

## **Detent Quantity:**

2

# Actuation Method:

Push button

#### Grip Length:

Between 5.000 inches and 5.020 inches

#### **Actuation Type:**

Pull and push

#### Hardness Rating:

58.0 rockwell c detent and 62.0 rockwell c detent

#### Shear Strength:

8200 double pounds per square inch

## Shoulder To Head End Distance:

1.270 inches

## Pin Center To Handle End Distance:

1.490 inches

## **Pin Attachment Type:**

Ring

## Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

## Material:

Steel spring

## **Material Specification:**

Qq-w-470 federal specification single material response spring

#### Surface Treatment:

Passivate ring

## Surface Treatment Specification:

Qq-p-416 type 1 or 2 cl 3 federal specification 1st treatment response collar or qq-p-35 federal specification 2nd treatment response collar

## Style Designator:

L handle

# Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A212a0

# Mil-std (military Standard):

Mil-s-6758 spec.