

View Online at <https://aerobasegroup.com/nsn/5315-01-038-7313>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.250 inches and 1.275 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shear Strength:**

32800 double pounds per square inch

**Shoulder To Head End Distance:**

1.600 inches

**Pin Center To Handle End Distance:**

1.760 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Material:**

Steel spring

**Material Specification:**

Qq-w-470 federal specification single material response spring

**Surface Treatment:**

Passivate ring

**Surface Treatment Specification:**

Qq-p-416 type 1 or 2 cl 3 federal specification single treatment response collar or qq-p-35 federal specification 2nd treatment response collar

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.