

View Online at <https://aerobasegroup.com/nsn/5315-01-041-4901>

**Shank Diameter:**

0.600 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.625 inches and 2.645 inches

**Actuation Type:**

Push

**Hardness Rating:**

64.0 rockwell c shank

**Shoulder To Head End Distance:**

Between 2.500 inches and 2.700 inches

**Pin Center To Handle End Distance:**

6.000 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 1.620 inches and 1.660 inches

**Product Name:**

Pin, quick release, positive locking, "I" handle, single action, detent wrench/safety pin slotted

**Special Features:**

Shank and handle shall be capable of withstanding 360 in lbs torque in either direction over their entire length without yielding of material; indent, stamp or cast "lau-7 series in 1/4 inch characteriers on front of handle with mil-std-130; part shall be delivered with nas 1091-30 warner streamer assembly; indent, stamp or cast "slotted" on both sides of handle in 1/4 inch characters in accordance with mil-std-130; indent, stamp or cast "push" in 1/8 inch characters on from of handle in accordance with mil-std-130; break all sharp edges

**Material:**

Stainless steel

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0