

View Online at <https://aerobasegroup.com/nsn/5315-01-041-4901>

Shank Diameter:

0.600 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.625 inches and 2.645 inches

Actuation Type:

Push

Hardness Rating:

64.0 rockwell c shank

Shoulder To Head End Distance:

Between 2.500 inches and 2.700 inches

Pin Center To Handle End Distance:

6.000 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

Between 1.620 inches and 1.660 inches

Product Name:

Pin, quick release, positive locking, "I" handle, single action, detent wrench/safety pin slotted

Special Features:

Shank and handle shall be capable of withstanding 360 in lbs torque in either direction over their entire length without yielding of material; indent, stamp or cast "lau-7 series in 1/4 inch characteriers on front of handle with mil-std-130; part shall be delivered with nas 1091-30 warner streamer assembly; indent, stamp or cast "slotted" on both sides of handle in 1/4 inch characters in accordance with mil-std-130; indent, stamp or cast "push" in 1/8 inch characters on from of handle in accordance with mil-std-130; break all sharp edges

Material:

Stainless steel

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0