

View Online at <https://aerobasegroup.com/nsn/5315-01-050-9758>

First End Style:

Chamfered

Second End Style:

Slotted

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

0.070 inches

Second Hole Diameter:

0.070 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.120 inches and 0.130 inches

Center To Center Distance Between Holes:

Between 0.670 inches and 0.700 inches

Pinlength:

Between 0.940 inches and 0.950 inches

Pindiameter:

Between 0.1860 inches and 0.1900 inches

Second End Slot Width:

Between 0.037 inches and 0.050 inches

First End Taper Length:

0.030 inches

First End Slot Depth:

Between 0.029 inches and 0.045 inches

Second End Relationship With First End:

Not identical

First End Taper Angle:

45.0 degrees

Special Features:

Chamfer on slotted end 45 degrees nom by 0.030 in. Lg

Material:

Steel comp 1020 or steel comp 1025

Material Specification:

Astm a108 assn standard single material response

Surface Treatment:

Cadmium and chromium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0