

View Online at <https://aerobasegroup.com/nsn/5315-01-051-1610>

First End Style:

Oval

Overall Length:

0.846 inches

Diameter:

0.1567 inches

Effective Length:

0.147 inches

Undercut Diameter:

Between 0.123 inches and 0.127 inches

Undercut Width:

Between 0.366 inches and 0.375 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.046 inches and 0.051 inches

Second Hole Diameter:

Between 0.046 inches and 0.051 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.070 inches and 0.085 inches

Center To Center Distance Between Holes:

Between 0.706 inches and 0.716 inches

Second End Relationship With First End:

Identical

Hardness Rating:

30.0 rockwell c and 35.0 rockwell c

First End Location:

Both ends

First End Outer Radius:

Between 0.125 inches and 0.131 inches

Material:

Steel comp 1095 or steel comp 416

Material Specification:

Astm-a-675 assn standard single material response or ams 5610 assn standard single material response

Surface Treatment:

Phosphate manganese or passivate

Surface Treatment Specification:

Mil-p-16232, type m, class 1 with vv-l-800 oil treatment military specification single treatment response or qq-p-35 federal specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.