

View Online at <https://aerobasegroup.com/nsn/5315-01-051-1610>

**First End Style:**

Oval

**Overall Length:**

0.846 inches

**Diameter:**

0.1567 inches

**Effective Length:**

0.147 inches

**Undercut Diameter:**

Between 0.123 inches and 0.127 inches

**Undercut Width:**

Between 0.366 inches and 0.375 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.046 inches and 0.051 inches

**Second Hole Diameter:**

Between 0.046 inches and 0.051 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.070 inches and 0.085 inches

**Center To Center Distance Between Holes:**

Between 0.706 inches and 0.716 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

30.0 rockwell c and 35.0 rockwell c

**First End Location:**

Both ends

**First End Outer Radius:**

Between 0.125 inches and 0.131 inches

**Material:**

Steel comp 1095 or steel comp 416

**Material Specification:**

Astm-a-675 assn standard single material response or ams 5610 assn standard single material response

**Surface Treatment:**

Phosphate manganese or passivate

**Surface Treatment Specification:**

Mil-p-16232, type m, class 1 with vv-l-800 oil treatment military specification single treatment response or qq-p-35 federal specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-p-16232 spec.