NSN 5315-01-053-1550

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-053-1550

Head Diameter:

0.750 inches

Shank Diameter:

Between 0.2470 inches and 0.2495 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

4

Actuation Method:

Lever

Grip Length:

Between 1.200 inches and 1.220 inches

Actuation Type:

Pull and push

Features Provided:

Drive out feature

Hardness Rating:

54.0 rockwell c detent and 64.0 rockwell c detent

Shoulder To Head End Distance:

1.730 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

Ring handle

Specification Data:

80205-nas1354 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5315-01-053-1550

Quick Release Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard): Mil-s-6758 spec.

