# NSN 5315-01-053-5134

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-053-5134

### Head Diameter:

Between 0.360 inches and 0.450 inches

#### Shank Diameter:

Between 0.2331 inches and 0.2346 inches

# Ring Handle Diameter:

1.125 inches

# **Detent Quantity:**

2

# **Actuation Method:**

Lever

Grip Length:

0.5906 inches

#### **Actuation Type:**

Pull and push

#### **Features Provided:**

Lock open feature

# Hardness Rating:

58.0 rockwell c and 62.0 rockwell c

### Shoulder To Head End Distance:

0.935 inches

## Pin Attachment Type:

Hook

## **Detent To Tapered End Distance:**

0.410 inches

#### Material:

Steel toggle or steel comp 4130 toggle

### **Material Specification:**

Qq-w-470 federal specification single material response spring

### Surface Treatment:

Passivate handle

### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response toggle

#### **Style Designator:**

Ring handle

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A212a0

# NSN 5315-01-053-5134

Quick Release Pin - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.

