

NSN 5315-01-053-7106 Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-053-7106 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Shank Length:** 0.500 inches **Shoulder Diameter:** Between 0.368 inches and 0.370 inches **Shank Diameter:** Between 0.240 inches and 0.252 inches **Overall Length:** Between 1.355 inches and 1.395 inches First End Taper Length: 0.016 inches **Second End Taper Length:** 0.147 inches Second End Relationship With First End: Not identical Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Thread Size:** 0.250 inches **Second Shank Diameter:** 

Between 0.246 inches and 0.248 inches

**First End Location:** 

Threaded end

First End Taper Angle:

9.4 degrees

**Surface Finish:** 

125.000 microinches

**Second End Taper Angle:** 

45.0 degrees

Second Shank Length:

0.625 inches

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

## NSN 5315-01-053-7106

A212a0

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: