

NSN 5315-01-053-7106 Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-053-7106 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Shank Length:** 0.500 inches **Shoulder Diameter:** Between 0.368 inches and 0.370 inches **Shank Diameter:** Between 0.240 inches and 0.252 inches **Overall Length:** Between 1.355 inches and 1.395 inches First End Taper Length: 0.016 inches **Second End Taper Length:** 0.147 inches Second End Relationship With First End: Not identical Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Thread Size:** 0.250 inches **Second Shank Diameter:**

Between 0.246 inches and 0.248 inches

First End Location:

Threaded end

First End Taper Angle:

9.4 degrees

Surface Finish:

125.000 microinches

Second End Taper Angle:

45.0 degrees

Second Shank Length:

0.625 inches

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

NSN 5315-01-053-7106

A212a0

Headless Shoulder Pin - Page 2 of 2



| Surface Treatment: |
|--|
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Style Designator: |
| Shoulder |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |