

View Online at <https://aerobasegroup.com/nsn/5315-01-056-8695>

**First End Style:**

Chamfered

**Second End Style:**

Pointed

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.320 inches

**Shank Length:**

0.329 inches

**Shoulder Width Across Flats:**

0.250 inches

**Shank Diameter:**

0.138 inches

**Overall Length:**

0.755 inches

**First End Taper Length:**

0.050 inches

**Second End Taper Length:**

0.125 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.164 inches

**Second Shank Diameter:**

0.138 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

125.000 microinches

**Second End Taper Angle:**

120.0 degrees

**Second Shank Length:**

0.380 inches

**Material:**

Steel comp 303

**Material Specification:**

Mil-s-7720, comp 303 cond b military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-7720 spec.