# NSN 5315-01-058-4317

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-058-4317

# Head Diameter:

Between 0.410 inches and 0.590 inches

# Shank Diameter:

Between 0.3095 inches and 0.3110 inches

# Ring Handle Diameter:

1.060 inches

# **Detent Quantity:**

2

## **Actuation Method:**

Lever

### Grip Length:

Between 1.000 inches and 1.020 inches

### Actuation Type:

Push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

# Shoulder To Head End Distance:

0.830 inches

# Pin Attachment Type:

Hook or ring

# Detent To Tapered End Distance:

Between 0.300 inches and 0.330 inches

#### Material:

Steel comp 4130 spindle

# Material Specification:

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

# Surface Treatment:

Cadmium spindle and chromate spindle

# Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

#### Style Designator:

Ring handle

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A212a0

# Mil-std (military Standard):

Mil-t-6736 spec.