# NSN 5315-01-059-9934

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-059-9934

Head	Sty	e.

Pan no. 2 (r1 not required in item description)

#### **Chamfer Length:**

Between 0.077 inches and 0.109 inches

Diameter:

Between 0.994 inches and 0.996 inches

#### **Under Head Length:**

Between 2.865 inches and 2.885 inches

#### **Hole Arrangement Style:**

One end drilled

#### First Hole Diameter:

Between 0.161 inches and 0.181 inches

#### Distance From Centerline Of Hole To End Of Pin:

0.196 inches

#### **Hardness Rating:**

26.5 rockwell c and 32.0 rockwell c

# Pin Chamfer Angle:

Between 14.5 degrees and 15.5 degrees

# **Shear Strength:**

117820 double pound

### **Pin Head Diameter:**

Between 1.171 inches and 1.203 inches

#### **Special Features:**

Shank end may have either a chamfer or radius at the option of the vendor

#### Height:

Between 0.109 inches and 0.141 inches

#### Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

#### **Material Specification:**

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response

#### **Surface Treatment:**

Cadmium

# **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Style Designator:**

Straight

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### Demilitarization:

No

# NSN 5315-01-059-9934

Headed Straight Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.