

View Online at <https://aerobasegroup.com/nsn/5315-01-061-8132>

**First End Style:**

Chamfered

**Second End Style:**

Radius

**Pinlength:**

Between 2.740 inches and 2.760 inches

**Pindiameter:**

Between 0.5001 inches and 0.5003 inches

**Second End Corner Radius:**

Between 0.063 inches and 0.167 inches

**First End Taper Length:**

0.572 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

36.0 rockwell c and 42.0 rockwell c

**Shear Strength:**

29000 double pound

**First End Taper Angle:**

Between 4.0 degrees and 16.0 degrees

**Surface Finish:**

16.0 microinches outside diameter

**Special Features:**

Chamfer 0.063 in. Min 0.167 in. Maximum lg 25 degrees optional in lieu of radius

**Material:**

Steel comp 410 or steel comp 416

**Material Specification:**

Astm a493 assn standard 1st material response or astm a582 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0