## NSN 5315-01-070-1632

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-070-1632 First End Style: Slotted **Second End Style:** Square **Shank Length:** 0.780 inches **Shoulder Diameter:** Between 0.3546 inches and 0.3550 inches **Shank Diameter:** Between 0.2497 inches and 0.2499 inches **Overall Length:** 1.357 inches **Undercut Diameter:** Between 0.184 inches and 0.194 inches **Undercut Width:** 0.060 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.0620 inches and 0.0624 inches **Distance From Centerline Of Hole To End Of Pin:** 0.450 inches First End Slot Width: 0.062 inches First End Slot Depth: 0.070 inches Second End Relationship With First End: Not identical **Hardness Rating:** 51.0 rockwell c and 57.0 rockwell c First End Location: Shoulder end **Surface Finish:** 32.0 microinches outside diameter Material: Steel comp 440c **Material Specification:** Qq-s-763 cond a federal specification single material response **Style Designator:** 

Undercut **Shelf Life:** N/a

## NSN 5315-01-070-1632

Headless Shoulder Pin - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A212a0