NSN 5315-01-071-8873

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-071-8873 First End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.935 inches **Shank Length:** 1.045 inches **Shoulder Diameter:** Between 0.484 inches and 0.500 inches **Shank Diameter:** Between 0.360 inches and 0.375 inches **Overall Length:** 3.250 inches **Undercut Diameter:** 0.290 inches **Undercut Width:** 0.130 inches **Second Undercut Width:** Any acceptable **Second Undercut Diameter:** Any acceptable **Hole Arrangement Style:** One end drilled First Hole Diameter: 0.127 inches Distance From Centerline Of Hole To End Of Pin: 0.342 inches First End Taper Length: Between 0.045 inches and 0.075 inches Second End Relationship With First End: Identical **Thread Size:** 0.375 inches **Second Shank Diameter:** Any acceptable **First End Location:** Both ends First End Taper Angle:

45.0 degrees

NSN 5315-01-071-8873 Headless Shoulder Pin - Page 2 of 2



| Second Shank Length: |
|--|
| 1.935 inches |
| Material: |
| Steel comp 1010 |
| Material Specification: |
| Qq-s-634 federal specification single material response or qq-s-631 federal specification single material response |
| Style Designator: |
| Undercut |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |