

View Online at <https://aerobasegroup.com/nsn/5315-01-073-4084>

First End Style:

Chamfered

Second End Style:

Counterbored w/o through hole

Shank Length:

0.620 inches

Shoulder Diameter:

0.750 inches

Shank Diameter:

Between 0.498 inches and 0.502 inches

Overall Length:

3.880 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.188 inches and 0.192 inches

Second Hole Diameter:

Between 0.188 inches and 0.192 inches

Distance From Centerline Of Hole To End Of Pin:

0.688 inches

Center To Center Distance Between Holes:

2.875 inches

Second End Counterbore Diameter:

Between 0.503 inches and 0.507 inches

Second End Counterbore Depth:

1.120 inches

First End Taper Length:

0.060 inches

Second End Relationship With First End:

Not identical

First End Location:

Short shank end

First End Taper Angle:

45.0 degrees

Special Features:

Block is included to end of pin; o/a length 0.840 in; o/a width 0.500 in; o/a thickness 0.500 in; with threaded 0.250 in diameter hole

Material:

Steel comp 1015

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response or qq-z-325 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0