

View Online at <https://aerobasegroup.com/nsn/5315-01-076-5118>

Head Diameter:

Between 0.360 inches and 0.450 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Grip Length:

Between 5.800 inches and 5.820 inches

Actuation Type:

Pull and push

Shoulder To Head End Distance:

0.935 inches

Detent To Tapered End Distance:

0.410 inches

Product Name:

Pin, quick release, positive locking, double acting, ring handle

Special Features:

Button cres302 or 303 per qq-s-763 or astm a484 or astm a582; attaching link band cres 17-7ph or cres 303 per qq-s-766; heat treatment, shank and spindle per mil-h-6875, cond. H-1000 for cress17-4ph and condition ch-900 for ph15-7mo, rockwell c40

Material:

Steel comp 631 spring or steel comp 302 spring

Material Specification:

As-5678 assn standard single material response spring or astma313, class1 assn standard single material response spring

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Ring handle

Specification Data:

80205-nas-17990 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0