

View Online at <https://aerobasegroup.com/nsn/5315-01-076-5118>

**Head Diameter:**

Between 0.360 inches and 0.450 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Grip Length:**

Between 5.800 inches and 5.820 inches

**Actuation Type:**

Pull and push

**Shoulder To Head End Distance:**

0.935 inches

**Detent To Tapered End Distance:**

0.410 inches

**Product Name:**

Pin, quick release, positive locking, double acting, ring handle

**Special Features:**

Button cress302 or 303 per qq-s-763 or astm a484 or astm a582; attaching link band cress 17-7ph or cress 303 per qq-s-766; heat treatment, shank and spindle per mil-h-6875, cond. H-1000 for cress17-4ph and condition ch-900 for ph15-7mo, rockwell c40

**Material:**

Steel comp 631 spring or steel comp 302 spring

**Material Specification:**

As-5678 assn standard single material response spring or astma313, class1 assn standard single material response spring

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas-17990 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0