

View Online at <https://aerobasegroup.com/nsn/5315-01-083-4242>

**Shank Diameter:**

Between 0.1870 inches and 0.1885 inches

**Button Handle Diameter:**

1.200 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.300 inches and 0.320 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

4600 double pounds per square inch

**Shoulder To Head End Distance:**

0.830 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 0.180 inches and 0.280 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

Button

**Specification Data:**

26512-g+510 manufacturers specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6736 spec.