## NSN 5315-01-086-6572

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-086-6572 **Head Diameter:** 0.750 inches **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Ring Handle Diameter:** 1.079 inches **Actuation Method:** Push button **Grip Length:** Between 0.200 inches and 0.220 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c shank and 40.0 rockwell c shank **Shear Strength:** 8200 double pounds per square inch **Shoulder To Head End Distance:** 1.490 inches Pin Attachment Type: Ring or hook **Detent To Tapered End Distance:** 0.380 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1334 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A212a0

## NSN 5315-01-086-6572

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.