## NSN 5315-01-086-9475

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-086-9475

First Frid Style:
First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
3a Thread Directions
Thread Direction:
Right-hand
Thread Length:
20.000 inches
Shank Length:
0.880 inches
Shoulder Width Across Flats:
0.970 inches
Shank Diameter:
0.748 inches
Overall Length:
6.430 inches
Undercut Diameter:
0.745 inches
Undercut Width:
0.090 inches
First End Taper Length:
0.060 inches
Second End Taper Length:
1.620 inches
Second End Relationship With First End:
Not identical
Hardness Rating:
40.0 rockwell c and 43.0 rockwell c
Thread Size:
0.500 inches
Second Shank Diameter:
1.060 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Second End Tip Radius:
0.120 inches
Second End Taper Angle:
25.0 degrees

## NSN 5315-01-086-9475

Headless Shoulder Pin - Page 2 of 2

Second Shank Length:

4.930 inches

Material:

Steel comp 4130

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

