NSN 5315-01-087-7616

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-087-7616 **Head Diameter:** Between 0.640 inches and 0.755 inches Handle Length: Between 2.125 inches and 2.250 inches Shank Diameter: Between 0.4970 inches and 0.4985 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 1.700 inches and 1.720 inches **Actuation Type:** Pull and push **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 32800 double pounds per square inch **Shoulder To Head End Distance:** 1.270 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** 0.590 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle or mil-t-6736 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response spindle **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A212a0

NSN 5315-01-087-7616

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.