# NSN 5315-01-089-2674

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-089-2674

# Shank Diameter:

Between 0.1870 inches and 0.1885 inches

# **Button Handle Diameter:**

Between 0.250 inches and 0.310 inches

# **Detent Quantity:**

2

## **Actuation Method:**

Push button

#### Grip Length:

Between 2.600 inches and 2.620 inches

## Actuation Type:

Push

## Hardness Rating:

40.0 rockwell c spindle

## Shear Strength:

5150 double pounds per square inch

## Shoulder To Head End Distance:

0.830 inches

# Pin Attachment Type:

Hook or ring

# Detent To Tapered End Distance:

Between 0.230 inches and 0.260 inches

#### Material:

Steel comp 630 spindle or steel comp 632 spindle

# **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

# Style Designator:

Button

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A212a0