

View Online at <https://aerobasegroup.com/nsn/5315-01-091-7032>

**Shank Diameter:**

Between 0.2470 inches and 0.2495 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.500 inches and 2.520 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank

**Shear Strength:**

9200 double pounds per square inch

**Shoulder To Head End Distance:**

1.550 inches

**Pin Center To Handle End Distance:**

1.780 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

0.380 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Specification Data:**

80205-nas1334 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0