

View Online at <https://aerobasegroup.com/nsn/5315-01-092-0334>

**Shank Diameter:**

Between 0.6220 inches and 0.6235 inches

**Button Handle Diameter:**

Between 1.530 inches and 1.700 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 6.500 inches and 7.500 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 3.000 inches and 3.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

57500 double pounds per square inch

**Shoulder To Head End Distance:**

1.500 inches

**Pin Attachment Type:**

Cord lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.550 inches and 0.580 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0