

View Online at <https://aerobasegroup.com/nsn/5315-01-092-1127>

**Head Diameter:**

0.750 inches

**Shank Diameter:**

Between 0.1870 inches and 0.1895 inches

**Ring Handle Diameter:**

1.800 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.600 inches and 0.620 inches

**Actuation Type:**

Push and pull

**Features Provided:**

Drive out feature

**Hardness Rating:**

40.0 rockwell c shank

**Shear Strength:**

5150 double pounds per square inch

**Shoulder To Head End Distance:**

1.730 inches

**Pin Attachment Type:**

Hook and ring

**Detent To Tapered End Distance:**

0.410 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas1353 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0