

View Online at <https://aerobasegroup.com/nsn/5315-01-093-0410>

**First End Style:**

Chamfered

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.281 inches and 0.291 inches

**Second Hole Diameter:**

Between 0.281 inches and 0.291 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.640 inches

**Center To Center Distance Between Holes:**

Between 9.770 inches and 9.790 inches

**Pinlength:**

11.060 inches

**Pindiameter:**

Between 0.9920 inches and 0.9950 inches

**First End Taper Length:**

0.380 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**First End Taper Angle:**

15.0 degrees

**Surface Finish:**

63.0 microinches outside diameter

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8640 or steel comp 8740

**Material Specification:**

Astm a322 assn standard 1st material response or astm a331 assn standard 2nd material response

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Mil-p-16232 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-p-16232 spec.