

View Online at <https://aerobasegroup.com/nsn/5315-01-093-0410>

First End Style:

Chamfered

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.281 inches and 0.291 inches

Second Hole Diameter:

Between 0.281 inches and 0.291 inches

Distance From Centerline Of Hole To End Of Pin:

0.640 inches

Center To Center Distance Between Holes:

Between 9.770 inches and 9.790 inches

Pinlength:

11.060 inches

Pindiameter:

Between 0.9920 inches and 0.9950 inches

First End Taper Length:

0.380 inches

Second End Relationship With First End:

Identical

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

First End Taper Angle:

15.0 degrees

Surface Finish:

63.0 microinches outside diameter

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8640 or steel comp 8740

Material Specification:

Astm a322 assn standard 1st material response or astm a331 assn standard 2nd material response

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Mil-p-16232 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.