

View Online at <https://aerobasegroup.com/nsn/5315-01-093-7340>

Head Diameter:

Between 0.610 inches and 0.640 inches

Shank Diameter:

Between 0.4950 inches and 0.4980 inches

Ring Handle Diameter:

1.187 inches

Detent Quantity:

2

Lanyard Length:

Between 11.500 inches and 12.500 inches

Grip Length:

Between 1.300 inches and 1.320 inches

Actuation Type:

Pull and push

Shoulder To Head End Distance:

0.562 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.516 inches

Material:

Steel comp 301 shank or steel comp 302 shank or steel comp 302b shank or steel comp 303 shank or steel comp 303se shank or steel comp 304 shank or steel comp 304l shank or steel comp 305 shank or steel comp 308 shank or steel comp 309 shank or steel comp 309s shank or steel comp 310 shank or steel comp 310s shank or steel comp 314 shank or steel comp 316 shank or steel comp 316f shank or steel comp 316l shank or steel comp 317 shank or steel comp 317l shank or steel comp 321 shank or steel comp 347 shank or steel comp 348 shank or steel comp 384 shank or steel comp 385 shank or steel comp 303f shank or steel comp 303s shank or steel comp 323 shank or steel comp 324 shank

Material Specification:

Qq-s-763 federal specification all material responses shank

Surface Treatment:

Passivate shank

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0