## NSN 5315-01-098-7349

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-098-7349 First End Style: Slotted **Second End Style:** Square **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.243 inches **Shank Length:** 0.263 inches **Shoulder Diameter:** Between 0.184 inches and 0.190 inches **Shank Diameter:** 0.138 inches **Overall Length:** 1.090 inches **Undercut Width:** 0.030 inches First End Slot Width: Between 0.033 inches and 0.043 inches First End Slot Depth: 0.050 inches Second End Relationship With First End: Not identical **Thread Size:** 0.138 inches **Second Shank Diameter:** Between 0.175 inches and 0.185 inches First End Location: Unthreaded end **Second Shank Length:** 0.650 inches **Special Features:** 0.137 in. Min 0.143 in. Maximum dia. Hole, 0.650 in. Deep drilled in slotted end parallel to longitudinal axis Material: Steel comp 303 **Material Specification:** 

**Surface Treatment: Passivate** 

Astm a582 assn standard single material response

## NSN 5315-01-098-7349

Headless Shoulder Pin - Page 2 of 2



Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0