NSN 5315-01-099-2709

Headless Shoulder Pin - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5315-01-099-2709



First End Style: Chamfered Second End Style: Slotted **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Any acceptable **Shank Length:** 0.380 inches **Shoulder Diameter:** Between 0.184 inches and 0.190 inches **Shank Diameter:** Between 0.133 inches and 0.143 inches **Overall Length:** 1.160 inches Second End Slot Width: 0.030 inches First End Taper Length: 0.020 inches **Second End Slot Depth:** 0.060 inches Second End Relationship With First End: Not identical **Thread Size:** 0.138 inches **Second Shank Diameter:** Between 0.122 inches and 0.128 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees **Second End Outer Radius:** Any acceptable

Special Features:

0.750 inches

Second Shank Length:

With groove 0.087 in. From shoulder on threaded end

Material:

Steel comp 303

NSN 5315-01-099-2709

Headless Shoulder Pin - Page 2 of 2



Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0