NSN 5315-01-099-2709

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-099-2709

First End Style:
Chamfered
Second End Style:
Slotted
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Any acceptable
Shank Length:
0.380 inches
Shoulder Diameter:
Between 0.184 inches and 0.190 inches
Shank Diameter:
Between 0.133 inches and 0.143 inches
Overall Length:
1.160 inches
Second End Slot Width:
0.030 inches
First End Taper Length:
0.020 inches
Second End Slot Depth:
0.060 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.138 inches
Second Shank Diameter:
Between 0.122 inches and 0.128 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Second End Outer Radius:
Any acceptable
Second Shank Length:
0.750 inches
Special Features:
With groove 0.087 in. From shoulder on threaded end
Material:

Steel comp 303

NSN 5315-01-099-2709

Headless Shoulder Pin - Page 2 of 2



Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0