# NSN 5315-01-101-6208

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-101-6208

## Shank Diameter:

Between 0.187 inches and 0.190 inches

## **Button Handle Diameter:**

1.203 inches

## **Actuation Method:**

Push button

#### Grip Length:

Between 0.600 inches and 0.620 inches

## Actuation Type:

Push

## Hardness Rating:

54.0 rockwell c detent and 64.0 rockwell c detent

## Shear Strength:

4600 double pounds per square inch

## Shoulder To Head End Distance:

1.547 inches

## Pin Attachment Type:

Hook or ring

## **Detent To Tapered End Distance:**

0.375 inches

# Material:

Steel uns k08500 spring

## Material Specification:

Qq-w-470 federal specification single material response spring

## Surface Treatment:

Passivate spring

## Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response spindle

## Style Designator:

Button

## **Specification Data:**

80205-nas1333 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A212a0

# Mil-std (military Standard):

Mil-s-6736 spec.