

View Online at <https://aerobasegroup.com/nsn/5315-01-103-2719>

**First End Style:**

Square

**Second End Style:**

Chamfered and counterbored

**Shank Length:**

0.030 inches

**Shoulder Diameter:**

0.164 inches

**Shank Diameter:**

0.093 inches

**Overall Length:**

0.625 inches

**Internal Drive Style:**

Slot

**Second End Counterbore Diameter:**

0.030 inches

**Second End Counterbore Depth:**

0.030 inches

**Second End Taper Length:**

0.015 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

55.0 rockwell c and 60.0 rockwell c

**Second Shank Diameter:**

0.093 inches

**First End Location:**

Square end

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

0.250 inches

**Special Features:**

Shoulder is threaded with a 8-32 unc-2a thread full lg

**Material:**

Steel comp 440c

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

-11-f-14072, finish e300 military specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

spec.