

View Online at <https://aerobasegroup.com/nsn/5315-01-110-5474>

**First End Style:**

Chamfered and countersunk

**Second End Style:**

Chamfered and countersunk

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

0.1246 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.875 inches

**Pinlength:**

3.310 inches

**Pindiameter:**

0.3750 inches

**First End Taper Length:**

0.030 inches

**Second End Taper Length:**

0.030 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Pin Grip Length:**

2.810 inches

**Surface Finish:**

125.0 microinches

**Second End Taper Angle:**

45.0 degrees

**Special Features:**

Drill and csk size no. 1 both ends optional

**Material:**

Steel comp 1040

**Material Specification:**

Astm-a-108 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 cl3 tyii federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0