

View Online at <https://aerobasegroup.com/nsn/5315-01-114-3938>

Grip Length:

3.300 inches

Overall Width:

1.370 inches

Lanyard Length:

12.500 inches

Actuation Method:

Push button

End Application:

F-18

Shear Strength:

23453 single pound

Pin Attachment Type:

Cable lanyard w/terminations

Pin Diameter:

0.621 inches

Shoulder To Head End Distance:

1.000 inches

Product Name:

Pin, expandable-quick release, assembly, engine aft mount

Special Features:

Assembly includes a lanyard 12.5 in long; locking pin 0.80 in; cam pivot pin, 1.000 in diameter with .625 hex both sides; lanyard lug, safety retention ring and spring

Material:

Stainless steel

Style Designator:

Closed position

Supplementary Features:

Pin shall be capable of 1000 locking cycles when engaged in a tolerance hole, without varying the cam rotation force by more than 20 percent; mechanical means for retaining the cam in the installed position; lanyard shall be permanently attached to the pin in a manner that will not interfere with its operation; pin shall be incapable of operation if the safety retention ring is engaged in the hole; the retention device shall be capable of unlatching with a maximum load of 3 to 5 lbs applied to the finger release provision; .75 lbs weight inc. Lanyard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0