

View Online at <https://aerobasegroup.com/nsn/5315-01-116-7902>

First End Style:

Chamfered

Head Style:

Thumb no. 4

Under Head Length:

Between 5.235 inches and 5.265 inches

First Step Diameter:

Between 0.707 inches and 0.709 inches

First Step Length:

Between 1.142 inches and 1.162 inches

Second Step Diameter:

0.625 inches

Second Step Length:

1.201 inches

Third Step Diameter:

Between 0.540 inches and 0.542 inches

Third Step Length:

Between 1.862 inches and 1.877 inches

Head Width:

1.000 inches

First End Taper Length:

0.030 inches

Hardness Rating:

28.0 rockwell c and 35.0 rockwell c

First End Taper Angle:

45.0 degrees

Special Features:

Fourth step lg. Is 1.025 and is threaded 0.375-24unf-2asecond step is threaded 0.625-18unf-2 a

Height:

0.560 inches

Material:

Steel comp 1330 or steel comp 4130 or steel comp 4140 or steel comp 8630 or steel comp 8640

Material Specification:

Astm a322 assn standard single material response or astm a331 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl1 military specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-13924 spec.