

View Online at <https://aerobasegroup.com/nsn/5315-01-116-7902>

**First End Style:**

Chamfered

**Head Style:**

Thumb no. 4

**Under Head Length:**

Between 5.235 inches and 5.265 inches

**First Step Diameter:**

Between 0.707 inches and 0.709 inches

**First Step Length:**

Between 1.142 inches and 1.162 inches

**Second Step Diameter:**

0.625 inches

**Second Step Length:**

1.201 inches

**Third Step Diameter:**

Between 0.540 inches and 0.542 inches

**Third Step Length:**

Between 1.862 inches and 1.877 inches

**Head Width:**

1.000 inches

**First End Taper Length:**

0.030 inches

**Hardness Rating:**

28.0 rockwell c and 35.0 rockwell c

**First End Taper Angle:**

45.0 degrees

**Special Features:**

Fourth step lg. Is 1.025 and is threaded 0.375-24unf-2asecond step is threaded 0.625-18unf-2 a

**Height:**

0.560 inches

**Material:**

Steel comp 1330 or steel comp 4130 or steel comp 4140 or steel comp 8630 or steel comp 8640

**Material Specification:**

Astm a322 assn standard single material response or astm a331 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, cl1 military specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-c-13924 spec.