

View Online at <https://aerobasegroup.com/nsn/5315-01-117-0781>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.335 inches

**Shank Length:**

1.000 inches

**Shoulder Diameter:**

Between 0.485 inches and 0.490 inches

**Shank Diameter:**

Between 0.366 inches and 0.374 inches

**Overall Length:**

2.410 inches

**Second End Slot Width:**

0.040 inches

**First End Taper Length:**

Between 0.100 inches and 0.130 inches

**Second End Slot Depth:**

0.060 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**First End Location:**

Shoulder end

**First End Taper Angle:**

45.0 degrees

**Special Features:**

Shank undercut 0.125 w after threaded portion

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-225/8 temper t6 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.