NSN 5315-01-118-3210

Headless Shoulder Pin - Page 1 of 2



5	dioup
View Online at https://aerobasegroup.com/nsn/5315-01-118-3210	
First End Style:	
Countersunk	
Second End Style:	
Chamfered and countersunk	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.460 inches	
Overall Length:	
3.767 inches	
First Step Diameter:	
Between 0.5013 inches and 0.5016 inches	
First Step Length:	
1.720 inches	
Second Step Diameter:	
Between 0.2948 inches and 0.2980 inches	
Second Step Length:	
1.602 inches	
Third Step Diameter:	
Between 0.1828 inches and 0.1900 inches	
Third Step Length:	
0.445 inches	
Hole Arrangement Style:	
One end drilled	
First Hole Diameter:	
Between 0.094 inches and 0.097 inches	
Distance From Centerline Of Hole To End Of Pin:	
0.855 inches	
Second End Taper Length:	
Between 0.053 inches and 0.083 inches	
Second End Relationship With First End:	
Not identical	
Thread Size:	
0.190 inches	

60.0 degrees

First End Location:

Shoulder end

First End Countersink Angle:

Second End Countersink Angle:

60.0 degrees

NSN 5315-01-118-3210 Headless Shoulder Pin - Page 2 of 2



First End Countersink Diameter:	
0.250 inches	
Second End Taper Angle:	
45.0 degrees	
Second End Countersink Diameter:	
0.125 inches	
Material:	
Steel comp xm-13	
Material Specification:	
Ams 5629 assn standard single material response	
Style Designator:	
Shoulder	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A212a0	