

View Online at <https://aerobasegroup.com/nsn/5315-01-120-3398>

**First End Style:**

Square w/thru hole

**Second End Style:**

Chamfered w/thru hole

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Thread Length:**

0.464 inches

**Shank Length:**

0.560 inches

**Shoulder Diameter:**

1.000 inches

**Shank Diameter:**

Between 0.784 inches and 0.785 inches

**Overall Length:**

8.620 inches

**Undercut Diameter:**

0.656 inches

**Undercut Width:**

5.440 inches

**Hole Arrangement Style:**

One end w/two drilled holes

**First Hole Diameter:**

0.120 inches

**Second Hole Diameter:**

0.120 inches

**Distance From Centerline Of Hole To End Of Pin:**

1.970 inches

**Second End Taper Length:**

0.120 inches

**Thready Qty Per Inch (tpi):**

16

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

53.0 rockwell c

**Thread Size:**

0.750 inches

**Second Shank Diameter:**

Between 0.783 inches and 0.784 inches

**First End Location:**

Threaded end

**Surface Finish:**

125.0 microinches

**Second End Taper Angle:**

15.0 degrees

**Angle Between Centerline Of Holes:**

90.0 degrees

**Second Shank Length:**

2.500 inches

**Material:**

Steel comp 440c

**Material Specification:**

Qq-s-763, type440c military specification all material responses

**Style Designator:**

Undercut

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

spec.