## NSN 5315-01-120-8489

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-120-8489

First End Style:

Chamfered and counterbored

**Overall Length:** 

Between 6.350 inches and 6.410 inches

Diameter:

Between 4.496 inches and 4.498 inches

**Effective Length:** 

Between 5.090 inches and 5.150 inches

**Undercut Diameter:** 

Between 4.304 inches and 4.316 inches

**Undercut Width:** 

Between 1.200 inches and 1.250 inches

**Second Undercut Width:** 

Between 1.200 inches and 1.250 inches

First End Counterbore Diameter:

Between 0.970 inches and 1.030 inches

**Second End Counterbore Diameter:** 

Between 0.970 inches and 1.030 inches

First End Counterbore Depth:

Between 0.720 inches and 0.780 inches

**Second End Counterbore Depth:** 

Between 0.720 inches and 0.780 inches

First End Taper Length:

Between 0.470 inches and 0.530 inches

**Second End Taper Length:** 

Between 0.470 inches and 0.530 inches

Second End Relationship With First End:

Identical

**Hardness Rating:** 

45.0 rockwell c and 50.0 rockwell c

**Shear Strength:** 

140000 single pounds per square inch

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

**Second End Taper Angle:** 

45.0 degrees

Material:

Steel comp 4340

Style Designator:

Groove

## NSN 5315-01-120-8489

Headless Grooved Pin - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0