NSN 5315-01-121-5658

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-121-5658

| First End Style: |
|---|
| Chamfered |
| Overall Length: |
| Between 3.550 inches and 3.600 inches |
| Diameter: |
| Between 1.247 inches and 1.250 inches |
| Effective Length: |
| Between 3.120 inches and 3.125 inches |
| Undercut Diameter: |
| Between 1.140 inches and 1.165 inches |
| Undercut Width: |
| Between 0.090 inches and 0.096 inches |
| Second Undercut Width: |
| Between 0.090 inches and 0.096 inches |
| Hole Arrangement Style: |
| One end drilled |
| First Hole Diameter: |
| 0.125 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 1.800 inches |
| First End Taper Length: |
| 0.060 inches |
| Features Provided: |
| Casehardened |
| |
| Second End Relationship With First End: Identical |
| Hardness Rating: |
| 56.0 rockwell c and 63.0 rockwell c |
| First End Location: |
| Both ends |
| |
| First End Taper Angle: 45.0 degrees |
| Special Features: |
| 1 longitudinal hole 2 in. Deep, 0.250-28 unf 2b-thd and hole perpendicular to the axis intersecting the longitudinal hole |
| Material: |
| Steel comp 8617h |
| Style Designator: |
| Groove |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| UTITE OT MICASUIC. |

--

NSN 5315-01-121-5658

Headless Grooved Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0