

View Online at <https://aerobasegroup.com/nsn/5315-01-122-0576>

First End Style:

Chamfered

Head Style:

Double chamfer

Under Head Length:

1.406 inches

First Step Diameter:

Between 0.360 inches and 0.390 inches

First Step Length:

0.052 inches

Second Step Diameter:

Between 0.308 inches and 0.310 inches

Second Step Length:

Between 1.329 inches and 1.359 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.062 inches and 0.078 inches

Distance From Centerline Of Hole To End Of Pin:

0.657 inches

End Application:

Lw/s: ssbn mk-118 fire control sys; arleigh burke class ddg; emory s. Land class as; forrestal class cv; supply class aoe; seawolf class ssn; wasp class lhd; los angeles class ssn (688); ticonderoga class cg (47)

First End Taper Length:

0.035 inches

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

Between 0.735 inches and 0.765 inches

Special Features:

Undercut 0.249 in. Nom diameter 0.047 in. Min 0.078 in. Maximum wide located next to bearing surface of first step

Height:

Between 0.110 inches and 0.140 inches

Material:

Steel comp 1018

Material Specification:

Aisi assn standard single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Qq-c-320 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0