

View Online at <https://aerobasegroup.com/nsn/5315-01-122-0576>

**First End Style:**

Chamfered

**Head Style:**

Double chamfer

**Under Head Length:**

1.406 inches

**First Step Diameter:**

Between 0.360 inches and 0.390 inches

**First Step Length:**

0.052 inches

**Second Step Diameter:**

Between 0.308 inches and 0.310 inches

**Second Step Length:**

Between 1.329 inches and 1.359 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.062 inches and 0.078 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.657 inches

**End Application:**

Lw/s: ssbn mk-118 fire control sys; arleigh burke class ddg; emory s. Land class as; forrestal class cv; supply class aoe; seawolf class ssn; wasp class lhd; los angeles class ssn (688); ticonderoga class cg (47)

**First End Taper Length:**

0.035 inches

**First End Taper Angle:**

45.0 degrees

**Pin Head Diameter:**

Between 0.735 inches and 0.765 inches

**Special Features:**

Undercut 0.249 in. Nom diameter 0.047 in. Min 0.078 in. Maximum wide located next to bearing surface of first step

**Height:**

Between 0.110 inches and 0.140 inches

**Material:**

Steel comp 1018

**Material Specification:**

Aisi assn standard single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Qq-c-320 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0